

INSTALLATION INSTRUCTIONS



Step #1

Remove the cover from the box with two able-bodied people. Transport the cover to the end of the spa where you normally enter and place on the bar top/shell.

Step #2

Find the large manila envelope inside the box. Set aside the hardware, keys, and registration card. Read the written installation instructions.



Step #3

After undoing the plastic wrap, roll the cover out across the entire shell of the spa.

Note: Rolling the cover open and closed 3-4 additional times, will allow the cover to form and relax correctly.



Step #4

Simultaneously pull on the straps from both ends, stretching the cover. Next, walk around the entire perimeter of the spa, lifting up the skirt flap and ensuring that the cover is laying flat on the bar top.

INSTALLATION INSTRUCTIONS (Continued)





Step #5

Mounting the end strap receivers. Start at one end, lift up the skirt flap. There should be a slight overhang up to 1 inch on the underside of the cover. After confirming this, mount the end strap receivers so they are taut, fasten and lock into place.

Note: Allow for seasonal adjustment in the strap length. Do not mount female receivers with the straps at full extension.

Step #6

Walk to the opposite end of the spa and pull end straps taut. The internal frame should be completely domed, with a nice uniform arc. Next, mount all remaining receivers, fastened and lock.

Step #7

When rolling out your cover on top of the spa, please take notice that the cover frame [hoop rods] may be leaning one direction [left or right], or slightly off center. It is important to roll the cover against that lean a couple of times until the cover is predominantly center domed. Having the cover lean slightly to the left or the right on installation is not uncommon based on it being rolled up tight in a shipping container. Please go to our page link for more information on cover frame and center dome manipulation: https://bit.ly/3KYAEOL

INSTALLATION INSTRUCTIONS (Continued)

Step #8

Mounting the strap receivers on the long sides. Do a final walk around the swim ensuring that the cover seal is created, laying flat on all sides. Finish mounting the remaining receivers.



Step #9

Locking the cover and daily use. Every time you roll the cover closed, the end user should focus on pulling the end straps-taut, creating the center dome arc to a complete pitch. Always fasten and lock the cover on all sides with key.



Step #10

Demonstrate how to use End 2 End Cover. Click on the video "How to roll open & close". The video will demonstrate the proper technique for all end-users:

http://bit.ly/e2e-open-close

Step #11

Register with the manufacturer. The end-user must go online, complete and submit within 30 days the cover registration here: Register now by Clicking Here.

INSTALLATION INSTRUCTIONS (Continued)

Be sure to leave the cover in the closed position—ensuring the cover is latched down and locked on all sides—when your swim spa is not in use.

If the warning label on your E2E Cover is worn, torn, or otherwise illegible, contact us immediately at cs@e2ecover.com for a replacement.

In no event, shall E2E, LLC be liable for any direct, indirect, punitive, incidental, or special consequential damages whatsoever—to property or life—arising out of [or connected with] the use or misuse of its products. Nor are we liable.

Please read and understand the Installation Instructions, as well as any additional literature, included with your cover. It is the purchasing customers responsibility to securely mount/install the lockable strap receivers. Failure to properly install lockable Surelock® fasteners and secure the cover may void your warranty.

Further, E2E is not responsible for the improper use/application of accessories, tools, or products extrinsic to those manufactured and provided by the same.



U.S. Patent Number: 8,683,621; 9,885,192, and D780322 S1. Other Patents Pending.

For questions regarding the installation of the End 2 End Swim Spa Covers call (855) 583-8880 ext. 714